

**Amendments to the Claims:**

**This listing of claims will replace all prior versions and listings of claims in the above-identified application:**

**Listing of Claims:**

1. (currently amended) A system, comprising:  
a carrier adapted to support a disk drive;  
a drawer having a receptacle;  
a drive mechanism mounted in the receptacle;  
sensor means located in the receptacle for sensing the carrier;  
control means associated with the drawer, the drive mechanism, and the sensor means;  
wherein  
when the carrier is inserted into the receptacle, the sensor means senses the carrier  
and signals the control means to actuate the drive mechanism to engage  
and draw the carrier into the receptacle, such that the carrier is fully seated  
in the receptacle; ~~and wherein~~  
the carrier is unseated and ejected from the drawer by reversing the drive  
mechanism; and  
the drawer has a self-healing signal connector and a magnetic power coupling that  
are adapted to interconnect with like components on the disk drive.
2. (original) The system of claim 1, wherein the carrier has a recess containing a pin  
that is engaged by the drive mechanism.
3. (original) The system of claim 1 wherein the sensor means senses a magnet on the  
carrier.
4. (original) The system of claim 1 wherein the sensor means comprises a Hall-Effect  
sensor.

5. (currently amended) The system of claim 1 wherein the self-healing signal connector comprises ~~drawer has~~ a self-healing optical signal connector and a magnetic power coupling that are adapted to interconnect with like components on the disk drive.
6. (original) The system of claim 1 wherein the drive mechanism comprises a motor that drives a worm gear, and a cam that is driven by the worm gear to engage the carrier.
7. (canceled)
8. (currently amended) A disk drive library, comprising:  
a disk drive carrier having a magnet;  
a disk drive mounted in the carrier;  
a drawer having a receptacle;  
a drive mechanism mounted in the receptacle;  
a sensor located in the receptacle for sensing the magnet on the carrier;  
control means associated with the drawer, the drive mechanism, and the sensor; wherein  
when the carrier is partially inserted into the receptacle, the sensor senses the magnet and signals the control means to actuate the drive mechanism to engage and draw the carrier into the receptacle, such the carrier is fully seated in the receptacle and the disk drive is interconnected with the drawer; and wherein  
the carrier is unseated and ejected from the drawer by reversing the drive mechanism; and  
the drawer has a self-healing signal connector and a magnetic power coupling that interconnect with like components on the disk drive.
9. (original) The disk drive library of claim 8 wherein the carrier has a recess containing a pin that is engaged by the drive mechanism.
10. (original) The disk drive library of claim 8 wherein the sensor is a Hall-Effect sensor.

11. (currently amended) The disk drive library of claim 8 wherein the self-healing signal connector drawer ~~has comprises~~ a self-healing optical signal connector ~~and a magnetic power coupling that interconnect with like components on the disk drive.~~
12. (original) The disk drive library of claim 8 wherein the drive mechanism comprises a motor that drives a worm gear, and a cam that is driven by the worm gear to engage the carrier.
13. (currently amended) A method of interconnecting a disk drive system, said method comprising the steps of:
- [[a)] ]providing a carrier with a disk drive, and a drawer having a receptacle, a drive mechanism, and a sensor;
  - [[b)] ]inserting the carrier into the receptacle;
  - [[c)] ]sensing the carrier with the sensor;
  - [[d)] ]actuating the drive mechanism to engage and draw the carrier into the receptacle, such the carrier is fully seated in the receptacle; wherein said actuating comprises interconnecting self-healing signal connectors and magnetically coupling power connectors on the disk drive and the drawer and
  - [[e)] ]unseating and ejecting the carrier from the drawer by reversing the drive mechanism.
14. (currently amended) The method of claim 13 wherein said sensing step (c) comprises sensing a magnet on the carrier.
15. (currently amended) The method of claim 13 wherein said interconnecting self-healing signal connectors step (d) further comprises optically interconnecting said self-healing signal connectors ~~and magnetically coupling power connectors on the disk drive and the drawer.~~
16. (currently amended) The method of claim 13 wherein said actuating step (d) comprises driving a worm gear to rotate a cam to engage the carrier.
17. (canceled)